

**Carli Suspension**  
422 Jenks Circle,  
Corona, CA 92880



**Tech Support:**  
888-99-CARLI  
(888) 992-2754

## **CS-DLRC-14**

### **NOTE:**

---

We Recommend installation be performed by a trained professional. Please review the product instructions prior to attempting installation to ensure installer is equipped with all tools and capabilities necessary to complete the product installation. We recommend thoroughly reading the instructions at least twice prior to attempting Installation.

Before beginning disassembly of the vehicle, check the “What’s Included” section of the instructions to ensure you’ve received all parts necessary to complete installation. Further, verify that the parts received are PROPER TO YOUR application (year range, motor, etc.) to avoid potential down-time in correcting potential discrepancies. Any discrepancies will be handled by Carli Suspension and the correcting products will be shipped UPS Ground.

## **LIFETIME PRODUCT WARRANTY**

Carli Suspension provides a limited lifetime product warranty against defects in workmanship and materials from date of purchase to the original purchaser for all products produced by Carli Suspension. Parts not manufactured by, but made to Carli Suspension’s specifications by third party manufacturers will carry a warranty through their respective manufacturer. (i.e. King Shocks, Bilstein Shocks, Fox Shocks). Deaver Leaf Spring’s warranty will be processed by Carli Suspension.

Proof of purchase (from the original purchaser only) will be required to process any warranty claims. Carli Suspension products must be purchased for the listed Retail Price reflected by the price listed on the Carli Suspension Website at the time of purchase. Carli Suspension reserves the right to refuse warranty claims made by any customer refusing or unable to present proof of purchase, or presenting proof of purchase reflecting a price lower than Carli Suspension’s Retail Price at the time the item was purchased.

Carli Suspension’s Limited Lifetime Warranty excludes the following parts which are subject to wear: Track Bar Bushings, Track Bar Heim Joints, Limit Straps, Control Arm Bushings, Radius Arm Bushings, Shock Bushings, Sway Bar End Link Heim Joints, Shock Seals, Shock Bearings, and Corrosion on Shock Shafts or Bodies. These items will be warranted for a period of 60 days from the date of purchase only if determined to be installed properly signifying manufacturing defect. Carli Suspension cannot warrant a product’s cosmetic finish due to the varying extreme elements that may be encountered.

Any alterations, modifications, or improper installation, of the product will void this warranty. Products should be inspected for defect upon receipt and approved before installation. Any defect in NEW product will be warranted if returned before installation in its original packaging. Carli Suspension’s obligation under this warranty is limited to the repair or replacement of the defective product only. All costs of removal, installation or reinstallation, freight charges, incidental or consequential damage are expressly excluded from this warranty.

Carli Suspension is not responsible for damages and/or warranty of other vehicle parts related or non-related to the installed Carli Suspension product. This warranty shall not apply to any product that has been subjected to accident, negligence, alteration, abuse or misuse as determined by Carli Suspension. Carli Suspension reserves the right to refuse warranty claims if produced parts are combined and/or substituted with other aftermarket suspension products. Combination and/or substitution of other aftermarket suspension components may cause premature wear and/or product failure. Carli Suspension reserves the right to change/alter product without obligation to update any previously purchased products.

## What's Included

---

- Coil Springs

## Installation

---

1. Remove Front Shocks, Factory Track Bar, Sway Bar End Links, and Disconnect axle-side Brake Line Brackets
2. Droop out the front end with the truck supported by the frame rails.
3. Remove old coils and discard; keep the factory coil isolator.
4. Place the factory isolator onto the Carli Coils ensuring they're indexed correctly. The Carli writing should be right-side-up and there is a indent/stop against which the end of the coil sits. The isolator has an indexing point that installs into a hole in the coil bucket.

**NOTE:** The Coils are side specific, "D" – Driver, "P" - Passenger

**NOTE:** If a Carli system with remote reservoir shocks was purchased, the shown reservoir mount should be placed on top of the isolator during coil spring installation.



5. Compress the front suspension so the weight of the truck is on the spring and install Adjustable Carli Track Bar, Radius Arm Drop Brackets, Sway Bar Drop Brackets & Factory end links; then re-secure the Brake line brackets to the axle and install your Carli Front Shocks..